



EOS-1D X

Mark III

Specifications

Type							
Type	Digital, AF/AE single-lens reflex camera						
Image Processor	DIGIC X						
Recording Media	<p>CFexpress cards, Type B</p> <ul style="list-style-type: none"> • Dual CFexpress card slots • XQD, CFast, CF and SD cards not supported <table border="1" data-bbox="456 667 1362 743"> <thead> <tr> <th>Specifications</th> <th>CFexpress 1.0</th> <th>CFast 2.0</th> </tr> </thead> <tbody> <tr> <td>Maximum transfer speed</td> <td>1.97 GB/s</td> <td>600 MB/s</td> </tr> </tbody> </table> <p>CFexpress cards provide significantly faster read/write speeds than CFast or CF cards, supporting extensive still-image burst rates, and RAW video recording. <small>* Canon is an authorized licensee of the CFast 2.0™ trademark, which may be registered in various jurisdictions.</small></p>	Specifications	CFexpress 1.0	CFast 2.0	Maximum transfer speed	1.97 GB/s	600 MB/s
Specifications	CFexpress 1.0	CFast 2.0					
Maximum transfer speed	1.97 GB/s	600 MB/s					
Image Format	Approx. 36mm x 24mm (35mm Full-frame)						
Lens Mount	Canon EF Mount						
Compatible Lenses	Canon EF Lenses (excluding EF-S and EF-M lenses)						
Image Sensor							
Type	High-sensitivity, high-resolution, large single-plate full-frame CMOS sensor						
Effective Pixels	Approx. 20.1 megapixels						
Total Pixels	Approx. 21.4 megapixels						
Aspect Ratio	3:2 (Horizontal: Vertical)						
Color Filter System	RGB primary color filters						
Low Pass Filter	High Detail Low Pass Filter, breaking one incoming light ray into 16 rays at image sensor						
Dust Removal Feature	<p>(1) Self Cleaning Sensor Unit</p> <ul style="list-style-type: none"> • Self-cleaning can be done automatically when the power is turned on/off. • During manual cleaning ([Clean now]), the data for light spot correction is also obtained. <p>(2) Dust Delete Data acquisition and appending</p> <ul style="list-style-type: none"> • The coordinates of the dust adhering to the low-pass filter are detected by a test shot and appended to subsequent images. • The dust coordinate data appended to the image is used by the EOS software to automatically erase the dust spots. <p>(3) Manual cleaning</p>						
Recording System							
Recording Format	Design Rule for Camera File System 2.0 and EXIF 2.31* <small>* Supports time difference information</small>						

Image Format	Image type		Extension
	Stills	JPEG	JPG
		HEIF	HIF
		RAW	CR3
		C-RAW	
Movies	ALL-I, IPB	MP4	
	RAW	CRM	
Recording Pixels	JPEG (8bit), HEIF (10 bit), RAW (14 bit, Canon original)		
	Image quality		Resolution (Pixels)
	JPEG	L	Approx. 20.0 megapixels (5472 x 3648)
		M1	Approx. 12.7 megapixels (4368 x 2912)
		M2	Approx. 8.9 megapixels (3648 x 2432)
S		Approx. 5.0 megapixels (2736 x 1824)	
HEIF	L	Approx. 20 megapixels (5472 x 3648)	
RAW	RAW / C-RAW		
Backup Recording	N/A		
File Numbering	<p>The following three types of file numbers can be set:</p> <p>(1) Continuous numbering</p> <ul style="list-style-type: none"> The numbering of captured images continues even after you replace the card. <p>(2) Auto reset</p> <ul style="list-style-type: none"> When you replace the card, the numbering will be reset to start from 0001. If the new card already contains images, the numbering will continue from the last recorded image in the card. <p>(3) Manual reset</p> <ul style="list-style-type: none"> Resets the file number to 0001, and creates a new folder automatically. 		
RAW + JPEG/HEIF Simultaneous Recording	Simultaneous recording of any combination of RAW/C-RAW and JPEG or HEIF image-recording quality is supported.		
Color Space	sRGB, Adobe RGB		
Picture Style	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined 1–3* * [Standard] is the default setting for [User Def. 1–3]		
White Balance			
Settings	<p>Auto (Ambience priority/White priority), Daylight, Shade, Cloudy*¹, Tungsten Light, White Fluorescent Light, Flash (Auto Setting)*², Custom (Custom WB) 1–5*³, Color Temperature</p> <p>¹ Also effective in twilight and sunset. ² With an EX or EL-series Speedlite having the color temperature information transmission feature, the color temperature setting changes to match the color temperature when the flash is fired. Set to approx. 6000K if the flash unit does not have the color temperature communication feature. ³ [Select image on card], [Record and register WB], and [Edit WB name] are supported. HEIF image cannot be selected.</p>		
Auto White Balance	Option between ambience priority and white priority settings		
Color Temperature Compensation	<p>Blue/amber bias: ±9 levels Magenta/green bias: ±9 levels Corrected in reference to the current WB mode's color temperature.</p>		
Color Temperature Information Transmission	Provided		
Viewfinder			
Type	Eye-level SLR type, with pentaprism		
Coverage	Approx. 100% vertically and horizontally		
Magnification	Approx. 0.76x (-1m ⁻¹ with 50mm lens at infinity) / 35.1° angle of view		
AF Point Display	Illuminated red dot-matrix display		

Cropping Information Display	Displays reference lines in the Viewfinder only during (1:1) cropping when set to 6:6.														
Eye Point	Approx. 20mm (at -1m ⁻¹ from eyepiece lens center)														
Dioptic Adjustment Correction	-3.0 to +1.0 m ⁻¹ (diopter)														
Focusing Screen	Fixed														
Mirror	Quick-return half mirror														
Time Display	Provided * Time of day displayed in shutter speed/aperture area in viewfinder, when ISO button is pressed, during viewfinder shooting standby														
Viewfinder Information	<p>AF displays, with red dot-matrix illumination: 191 AF points; active AF Area; Zone AF brackets; Automatic AF point select brackets</p> <p>Exposure Displays: Manual mode icon; AE Lock icon; Flash ready icon; FEL icon; Shutter speed; Aperture; Exposure compensation scale; Frames remaining on card; ISO; Highlight Tone Priority (D+) active; AF confirmation icon; AI Servo AF active arrows</p> <p>Right side display: +/- 3-stop metering scale; Flash Exposure Compensation/FEL/Flash Metered Manual scale; Frames remaining in burst (0~99); JPEG/RAW icons; Battery level icon</p> <p>Displayed on focus screen, via LCD overlay: Spot metering circle; Electronic level display; Grid lines; Shooting mode; Metering mode; White Balance setting; Drive mode; AF Operation; Flicker Detection icon; Warning symbol; AF status indicator All except Spot meter circle can be displayed or not with [Show/Hide in viewfinder]</p>														
Depth Of Field Preview	Provided														
Autofocus															
Type	TTL secondary image-forming phase-difference detection system with High-res AF Sensor														
AF Points (Optical AF)	<p>Max. 191 points (Cross-type AF points: Max. 155 points)</p> <table border="1"> <thead> <tr> <th>AF Point type</th> <th>Maximum available AF points</th> </tr> </thead> <tbody> <tr> <td>Dual Cross-type AF Points at f/2.8 and f/5.6</td> <td>1</td> </tr> <tr> <td>Cross-type AF Points at f/4.0+f/5.6</td> <td>90</td> </tr> <tr> <td>Cross-type AF Points at f/5.6</td> <td>64</td> </tr> <tr> <td>AF Points at f/5.6</td> <td>36</td> </tr> <tr> <td>AF Points at f/8</td> <td>191</td> </tr> <tr> <td>Cross-type AF Points at f/8</td> <td>65</td> </tr> </tbody> </table> <p>The number of AF points, cross-type AF points and dual cross-type AF points vary depending on the lens used.</p>	AF Point type	Maximum available AF points	Dual Cross-type AF Points at f/2.8 and f/5.6	1	Cross-type AF Points at f/4.0+f/5.6	90	Cross-type AF Points at f/5.6	64	AF Points at f/5.6	36	AF Points at f/8	191	Cross-type AF Points at f/8	65
AF Point type	Maximum available AF points														
Dual Cross-type AF Points at f/2.8 and f/5.6	1														
Cross-type AF Points at f/4.0+f/5.6	90														
Cross-type AF Points at f/5.6	64														
AF Points at f/5.6	36														
AF Points at f/8	191														
Cross-type AF Points at f/8	65														
Focusing Brightness Range	<table border="1"> <thead> <tr> <th>AF Point</th> <th>Brightness</th> </tr> </thead> <tbody> <tr> <td>f/2.8 AF point at center</td> <td>EV -4 – 21</td> </tr> <tr> <td>f/5.6 AF point at center</td> <td>EV -3 – 21</td> </tr> <tr> <td>Peripheral f/5.6 AF points</td> <td>EV -1.5 – 21</td> </tr> </tbody> </table>	AF Point	Brightness	f/2.8 AF point at center	EV -4 – 21	f/5.6 AF point at center	EV -3 – 21	Peripheral f/5.6 AF points	EV -1.5 – 21						
AF Point	Brightness														
f/2.8 AF point at center	EV -4 – 21														
f/5.6 AF point at center	EV -3 – 21														
Peripheral f/5.6 AF points	EV -1.5 – 21														
AF Operation	<p>(1) Autofocus</p> <ol style="list-style-type: none"> One-Shot AF AI Servo AF <p>(2) Manual focus</p>														
Electronic Full-time Manual Focus	<p>When using a compatible lens, manual focusing will always become possible with the electric focusing ring.</p> <p>Disable/Enable</p> <p>Compatible Lenses: EF400mm f/2.8L IS III USM, EF600mm f/4L IS III USM</p>														

AF Area Settings	<p>Manually-selected AF Areas</p> <ul style="list-style-type: none"> • Spot AF • Single-point AF • AF point Expansion (4-point surround) • AF point Expansion (8-point surround) • Zone AF • Large Zone AF (all AF points divided into three large zones) <p>Automatic AF point selection (all AF points available; reference brackets around AF array)</p>						
AF Function Registration/Switching	Customizable with Custom Controls						
Subject Tracking Settings	<p>AF Priority (people): Enable / Disable</p> <p>Subject Switching: Disable / Enable (slow) / Enable</p>						
Selected AF Point Display	Red dot-matrix illumination of AF points, zone AF brackets, and Auto AF Area brackets						
Active AF Point Indicator	(1) Displayed in viewfinder area						
Eye Detection AF (Live View and Movie)	<p>Enables subject eye detection and AF when set to [Face+Tracking] and [Eye Detection AF: Enable].</p> <table border="1" data-bbox="456 804 1474 930"> <thead> <tr> <th colspan="2">Eye Selection</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Auto</td> <td>(1) Selects the eye closer to the camera (as detected from the angle of the face). (2) At the same distance from the camera, selects the eye closer to the center of the image.</td> </tr> <tr> <td style="text-align: center;">Manual</td> <td>(1) Selected by touching the eye in the face selection frame. (2) Can be selected with the Multi-controllers</td> </tr> </tbody> </table>	Eye Selection		Auto	(1) Selects the eye closer to the camera (as detected from the angle of the face). (2) At the same distance from the camera, selects the eye closer to the center of the image.	Manual	(1) Selected by touching the eye in the face selection frame. (2) Can be selected with the Multi-controllers
Eye Selection							
Auto	(1) Selects the eye closer to the camera (as detected from the angle of the face). (2) At the same distance from the camera, selects the eye closer to the center of the image.						
Manual	(1) Selected by touching the eye in the face selection frame. (2) Can be selected with the Multi-controllers						
AF Assist Beam	<p>When an external EOS-dedicated Speedlite is attached to the camera, the following options are available:</p> <ol style="list-style-type: none"> (1) Enable (2) Disable (3) IR AF assist beam only 						
Exposure Control							
Metering Modes	<p>Optical Viewfinder: 216-zone (18 x 12) metering with approx. 400,000-pixel RGB+IR metering sensor.</p> <p>Live View: 384-zone (24 x 16) metering using image sensor output signals</p> <p>The following metering modes selectable:</p> <ol style="list-style-type: none"> (1) Evaluative metering (linked to all AF points) (2) Partial metering (Viewfinder: Approx. 6.2% of the screen) (Live View: Approx. 5.8% of the screen) (3) Spot metering (center, approx. 1.5% of viewfinder) (Live View: Approx. 2.9% of the screen) <ol style="list-style-type: none"> 1. Center spot metering 2. AF point-linked spot metering (Custom Function) <ul style="list-style-type: none"> • Linkable to all AF points. • With automatic AF point selection, center spot metering will apply. 3. Multi-spot metering (Optical Viewfinder only) (4) Center-weighted average metering <ul style="list-style-type: none"> • The selectable metering modes can be restricted (Custom Function). 						
Metering Range	<p>At 73°F/23°C, ISO 100, with evaluative metering:</p> <p>EV 0–20 (Optical Viewfinder)</p> <p>EV -3–20 (Live View)</p> <p>EV -1–20 (Movie Recording)</p>						
Exposure Control Systems	<ol style="list-style-type: none"> (1) Program AE (Shiftable) (2) Shutter-priority AE (Safety shift possible) (3) Aperture-priority AE (Safety shift possible) (4) Manual exposure <ul style="list-style-type: none"> • The metering mode can be specified. (5) Bulb (6) Three custom shooting modes 						

ISO Speed Range	<p>Manual setting</p> <table border="1"> <tr> <td>Normal ISO Speeds</td> <td>ISO 100–102400 (in 1/3-stop increments)</td> </tr> <tr> <td>Expanded ISO Speeds (Equivalent)</td> <td>L: 50, H1: 204800, H2: 409600, H3: 819200</td> </tr> </table> <p>Highlight Tone Priority: ISO range 200–102400. Expanded ISO cannot be set during HDR shooting.</p> <p>Auto ISO setting</p> <table border="1"> <thead> <tr> <th rowspan="2">Shooting Mode</th> <th colspan="2">ISO Settings</th> </tr> <tr> <th>No Flash</th> <th>With Flash</th> </tr> </thead> <tbody> <tr> <td>P, Tv, Av, M</td> <td>ISO 100¹–102400²</td> <td>ISO 100¹–6400^{2,3}</td> </tr> <tr> <td>During Bulb shooting</td> <td colspan="2">ISO 400 fixed⁴</td> </tr> </tbody> </table> <p>¹ ISO 200 when [Highlight tone priority] is set to [Enable] or [Enhanced]. ² Varies depending on [Maximum] and [Minimum] of [Auto range]. ³ ISO 1600 when using a lens that is not compatible with "Variable control of maximum ISO Auto limit for E-TTL". ⁴ If outside the setting range, changed to the value closest to ISO 400.</p>	Normal ISO Speeds	ISO 100–102400 (in 1/3-stop increments)	Expanded ISO Speeds (Equivalent)	L: 50, H1: 204800, H2: 409600, H3: 819200	Shooting Mode	ISO Settings		No Flash	With Flash	P, Tv, Av, M	ISO 100 ¹ –102400 ²	ISO 100 ¹ –6400 ^{2,3}	During Bulb shooting	ISO 400 fixed ⁴	
	Normal ISO Speeds	ISO 100–102400 (in 1/3-stop increments)														
Expanded ISO Speeds (Equivalent)	L: 50, H1: 204800, H2: 409600, H3: 819200															
Shooting Mode	ISO Settings															
	No Flash	With Flash														
P, Tv, Av, M	ISO 100 ¹ –102400 ²	ISO 100 ¹ –6400 ^{2,3}														
During Bulb shooting	ISO 400 fixed ⁴															
Exposure Compensation	<p>Adjusted by user: ±5 stops in 1/3- or 1/2-stop increments AEB: ±3 stops in 1/3- or 1/2-stop increments * Indicated up to ±3 stops on the LCD panel and in the viewfinder.</p>															
AE Lock	<p>(1) Auto AE lock • In the One-Shot AF mode with evaluative metering, AE lock takes effect when focus is achieved. (2) User-applied AE lock • With AE lock button in P, Av, Tv and M modes. (AE lock is updated each time you press the button.) • Enabled in all metering modes.</p>															
Auto Applying of AE Lock after Focusing	Configurable															
Shutter																
Type	<p>Vertical-travel, mechanical, focal-plane shutter with all speeds electronically-controlled • Live View: Mechanical, Electronic 1st-curtain, and Electronic shutter operation selectable</p>															
Shutter Speeds	<p>When [Mechanical] or [Elec. 1st-curtain] is set: 1/8000 to 30 sec., bulb When [Electronic] is set: 1/8000-0.5 sec. X-sync: 1/250 sec. • Available shutter speed range can be set via Custom Function • Flash shooting not possible during Electronic shutter operation</p>															
Shutter Release	Soft-touch electromagnetic release															
Self Timer	10-sec. delay, 2-sec. delay															
External Speedlite																
EOS Dedicated Speedlite	E-TTL II autoflash with all EX and EL Series Speedlites															
Zooming to Match Focal Length	Provided															
E-TTL Balance	Ambience Priority, Standard, Flash priority															
Flash Exposure Compensation	±3 stops in 1/3- or 1/2-stop increments															
FE Lock	Provided															
Continuous Flash Control	<p>(1) E-TTL each shot (New E-TTL reading for each exposure in a continuous sequence) (2) E-TTL 1st shot (Flash exposure locked for 2nd and subsequent exposures in a continuous sequence)</p>															

External Speedlite Control Menu	<p>Available for EX and EL series Speedlites.</p> <p>(1) General speedlite settings: Flash firing; E-TTL balance; E-TTL II metering; Continuous flash control; Flash sync speed in Av mode</p> <p>(2) Flash function settings: Flash exposure mode; Wireless flash control; Flash head zoom; Flash sync (1st/2nd curtain sync and High-speed sync); Flash exposure compensation; Flash exposure bracketing</p> <p>(3) Flash Custom Function settings</p>
PC Terminal	<p>Provided</p> <p>* No polarity.</p> <p>* Sync speed: Since the flash duration of studio flash units vary, set a sync speed within 1/125 sec. to 1/30 sec. and check if the flash sync works.</p> <p>* Both the accessory shoe (X-sync contact with maximum sync speed of 1/250 sec.) and the PC terminal can be used simultaneously for simultaneous flash firing.</p>
Drive System	
Drive Mode and Continuous Shooting Speed	<p>(1) Single shooting</p> <p>(2) High-speed continuous shooting*: Viewfinder: Max. approx. 16 shots/sec. (user-adjustable 16~3 fps) Live View Shooting: Max. approx. 20 shots/sec.</p> <p>(3) Continuous Shooting: Viewfinder: Max. approx. 10 shots/sec. (user-adjustable 15~2 fps) Live View Shooting*¹: Max. approx. 10 shots/sec.*²</p> <p>(4) Low-speed continuous shooting Viewfinder: Max. approx. 3 shots/sec. (user-adjustable 14~1 fps) Live View Shooting*¹: Max. approx. 3 shots/sec.</p> <p>(5) Silent single shooting</p> <p>(6) Silent high-speed continuous shooting Viewfinder: Max. approx. 8 shots/sec. (user-adjustable 8~2 fps) Live View Shooting*¹: Max. approx. 10 shots/sec.*²</p> <p>(7) Silent low-speed continuous shooting Viewfinder: Max. approx. 3 shots/sec. (user-adjustable 14~1 fps) Live View Shooting*¹: Max. approx. 3 shots/sec.</p> <p>*Continuous shooting speed may be slower under the following conditions: shutter speed, aperture, aperture status during continuous shooting, flash, anti-flicker shooting set to Enable, remaining battery level, temperature, subject conditions, brightness (shooting under low light, etc.), lens type, power source type, when internal memory is full (momentarily prevents shooting).</p> <p>*¹When the electronic shutter is used, the shooting speed of the continuous shooting becomes the same as the high-speed continuous shooting.</p> <p>*²When the mechanical shutter is used, the shooting speed of the continuous shooting will be approx. 8.0 shots/sec.</p>

Maximum Burst	The maximum burst during continuous shooting is as follows:			
	Image Quality	File Size [Approx. MB]	Possible Shots [Approx.]* ¹	Maximum Burst [Approx.]* ¹
	L	7.6	40,650	1,000 or more
	M1	5.4	56,960	1,000 or more
	M2	4.1	74,070	1,000 or more
	S	2.8	109,110	1,000 or more
	HEIF	7.6	39,650	1,000 or more
	RAW* ²	22.1	14,150	1,000 or more
	C-RAW* ²	13.1	27,560	1,000 or more
	RAW+L	22.1+7.6	10,500	1,000 or more
	C-RAW+L	13.1+7.6	16,420	1,000 or more
	RAW+M1	22.1+5.4	11,330	1,000 or more
	C-RAW+M1	13.1+5.4	18,570	1,000 or more
	RAW+M2	22.1+4.1	11,880	1,000 or more
	C-RAW+M2	13.1+4.1	20,080	1,000 or more
	RAW+S	22.1+2.8	12,530	1,000 or more
	C-RAW+S	13.1+2.8	22,000	1,000 or more
	RAW+HEIF	24.3+7.6	9,620	350
C-RAW+HEIF	13.7+7.6	14,380	420	
<p>* File size, number of possible shots, and maximum burst vary depending on shooting conditions (including JPEG/HEIF image quality: 8, subject, memory card brand, card storage capacity, ISO speed, Picture Style, and Custom Function, etc).</p> <p>¹ The number of possible shots and standard maximum burst apply to a compliant 325GB card based on Canon testing standards, in viewfinder shooting.</p> <p>² With [HDR PQ] set to [OFF].</p>				

Live View Functions	
Shooting Modes	Still photo and video recording
Focusing	(1) Dual Pixel CMOS AF <ul style="list-style-type: none"> • Dual Pixel CMOS AF is possible with all EF lenses. (2) Manual focus <ul style="list-style-type: none"> • Magnify the image by 5x or 10x and focus manually. • MF peaking and Focus Guide possible
Metering Modes	(1) Evaluative metering (linked to all AF points) (2) Partial metering: Approx. 5.8% of the screen (3) Spot metering: Approx. 2.9% of the screen (4) Center-weighted average metering AE lock possible. The active metering timer can be changed.
Metering Range	EV -3–20 (at 73°F/23°C, ISO 100, with evaluative metering)
Grid Display	(1) Off (2) 3x3 (3) 6x4 (4) 3x3+diag
Electronic (Silent) Shutter Operation	Possible with Shutter mode set to Electronic <ul style="list-style-type: none"> • Audible sounds possible from lens operation, etc. • Flash not possible when LV Shutter mode set to Electronic

HDR Shooting									
HDR Shooting (Still photo HDR PQ)	<table border="1"> <thead> <tr> <th>Recording Format</th> <th>Bit Depth</th> <th>Color Sampling Method</th> <th>HDR Standard</th> </tr> </thead> <tbody> <tr> <td>HEIF</td> <td>10 bit</td> <td>YCbCr 4:2:2</td> <td>ITU-R BT. 2100 (PQ)</td> </tr> </tbody> </table>	Recording Format	Bit Depth	Color Sampling Method	HDR Standard	HEIF	10 bit	YCbCr 4:2:2	ITU-R BT. 2100 (PQ)
	Recording Format	Bit Depth	Color Sampling Method	HDR Standard					
HEIF	10 bit	YCbCr 4:2:2	ITU-R BT. 2100 (PQ)						

HDR Shooting (HDR PQ)	Disable / Enable																																		
HDR Assist Display in Shooting & Playback	Exposure prior (mid-tones) / Tones prior (highlights)																																		
Video Shooting																																			
File Format: Canon Log	<p>Normal movie recording:</p> <ul style="list-style-type: none"> • MPEG4 H.264 / AVC • 8-bit, 4:2:0; Color space BT.709 <p>Canon Log recording:</p> <ul style="list-style-type: none"> • MPEG4 H.265 / HEVC • 10-bit, 4:2:2; Color space BT.709 / BT.2020 <p>Audio: AAC or Linear PCM (Audio Compression in C.Fn menu, during ALL-I or IPB recording)</p> <ul style="list-style-type: none"> • Internal monaural microphone • 3.5mm stereo external microphone jack 																																		
Recording Sizes and Format	<table border="1"> <thead> <tr> <th colspan="3">NTSC</th> </tr> </thead> <tbody> <tr> <td>5.5K RAW (5472 x 2886)</td> <td>59.94 fps* 29.97 fps 24.00 fps 23.98 fps</td> <td>RAW</td> </tr> <tr> <td>4K DCI (4096 x 2160)</td> <td>59.94 fps* 29.97 fps 24.00 fps 23.98 fps</td> <td>ALL-I IPB</td> </tr> <tr> <td>4K UHD (3840 x 2160)</td> <td>59.94 fps* 29.97 fps 23.98 fps[^]</td> <td>ALL-I IPB</td> </tr> <tr> <td>4K DCI (cropped) (4096 x 2160)</td> <td>59.94 fps 29.97 fps 24.00 fps 23.98 fps</td> <td>ALL-I IPB</td> </tr> <tr> <td rowspan="2">Full HD (1920 x 1080)</td> <td>119.90 fps** 59.94 fps 23.98 fps[^]</td> <td>ALL-I IPB</td> </tr> <tr> <td>29.97 fps</td> <td>ALL-I IPB IPB (Light)</td> </tr> </tbody> </table> <p>* AF does not function. ** Audio not recorded at High Frame Rate 119.90 fps recording [^] 24p recording will be supported through firmware update after shipping.</p>	NTSC			5.5K RAW (5472 x 2886)	59.94 fps* 29.97 fps 24.00 fps 23.98 fps	RAW	4K DCI (4096 x 2160)	59.94 fps* 29.97 fps 24.00 fps 23.98 fps	ALL-I IPB	4K UHD (3840 x 2160)	59.94 fps* 29.97 fps 23.98 fps [^]	ALL-I IPB	4K DCI (cropped) (4096 x 2160)	59.94 fps 29.97 fps 24.00 fps 23.98 fps	ALL-I IPB	Full HD (1920 x 1080)	119.90 fps** 59.94 fps 23.98 fps [^]	ALL-I IPB	29.97 fps	ALL-I IPB IPB (Light)														
NTSC																																			
5.5K RAW (5472 x 2886)	59.94 fps* 29.97 fps 24.00 fps 23.98 fps	RAW																																	
4K DCI (4096 x 2160)	59.94 fps* 29.97 fps 24.00 fps 23.98 fps	ALL-I IPB																																	
4K UHD (3840 x 2160)	59.94 fps* 29.97 fps 23.98 fps [^]	ALL-I IPB																																	
4K DCI (cropped) (4096 x 2160)	59.94 fps 29.97 fps 24.00 fps 23.98 fps	ALL-I IPB																																	
Full HD (1920 x 1080)	119.90 fps** 59.94 fps 23.98 fps [^]	ALL-I IPB																																	
	29.97 fps	ALL-I IPB IPB (Light)																																	
Focusing	<p>(1) Dual Pixel CMOS AF (2) Manual focus</p> <p>* Magnify the image by 5x or 10x and focus manually (not possible during movie shooting).</p>																																		
Movie Digital IS	<table border="1"> <thead> <tr> <th>Movie Digital IS Setting</th> <th>Full HD</th> <th>4K DCI</th> <th>4K UHD</th> <th>4K DCI Cropped</th> </tr> </thead> <tbody> <tr> <td>Item</td> <td>Disable</td> <td>Approx. 100%</td> <td>Approx. 100%</td> <td>Approx. 94%</td> <td>Approx. 75%</td> </tr> <tr> <td></td> <td>Enable</td> <td>Approx. 90%</td> <td>Approx. 90%</td> <td>Approx. 84%</td> <td>Approx. 67%</td> </tr> <tr> <td></td> <td>Enhanced</td> <td>Approx. 70%</td> <td>Approx. 70%</td> <td>Approx. 66%</td> <td>Approx. 52%</td> </tr> </tbody> </table> <p>* Cannot be used during RAW movie recording. * The angle of view remains at the specified setting, regardless of how the IS switch of IS lens is set.</p>	Movie Digital IS Setting	Full HD	4K DCI	4K UHD	4K DCI Cropped	Item	Disable	Approx. 100%	Approx. 100%	Approx. 94%	Approx. 75%		Enable	Approx. 90%	Approx. 90%	Approx. 84%	Approx. 67%		Enhanced	Approx. 70%	Approx. 70%	Approx. 66%	Approx. 52%											
Movie Digital IS Setting	Full HD	4K DCI	4K UHD	4K DCI Cropped																															
Item	Disable	Approx. 100%	Approx. 100%	Approx. 94%	Approx. 75%																														
	Enable	Approx. 90%	Approx. 90%	Approx. 84%	Approx. 67%																														
	Enhanced	Approx. 70%	Approx. 70%	Approx. 66%	Approx. 52%																														
Exposure Control	<table border="1"> <thead> <tr> <th rowspan="2">Shooting Mode</th> <th rowspan="2">Exposure Control</th> <th colspan="2">Shutter Speed (sec.)</th> <th colspan="2">Aperture</th> </tr> <tr> <th>Auto Setting</th> <th>Manual Setting</th> <th>Auto Setting</th> <th>Manual Setting</th> </tr> </thead> <tbody> <tr> <td>P, bulb</td> <td>Program AE for movie shooting</td> <td>Yes</td> <td>–</td> <td>Yes</td> <td>–</td> </tr> <tr> <td>Tv</td> <td>Movie shutter-priority AE</td> <td>–</td> <td>Yes</td> <td>Yes</td> <td>–</td> </tr> <tr> <td>Av</td> <td>Movie aperture-priority AE</td> <td>Yes</td> <td>–</td> <td>–</td> <td>Yes</td> </tr> <tr> <td>M</td> <td>Movie manual exposure</td> <td>–</td> <td>Yes</td> <td>–</td> <td>Yes</td> </tr> </tbody> </table>	Shooting Mode	Exposure Control	Shutter Speed (sec.)		Aperture		Auto Setting	Manual Setting	Auto Setting	Manual Setting	P, bulb	Program AE for movie shooting	Yes	–	Yes	–	Tv	Movie shutter-priority AE	–	Yes	Yes	–	Av	Movie aperture-priority AE	Yes	–	–	Yes	M	Movie manual exposure	–	Yes	–	Yes
Shooting Mode	Exposure Control			Shutter Speed (sec.)		Aperture																													
		Auto Setting	Manual Setting	Auto Setting	Manual Setting																														
P, bulb	Program AE for movie shooting	Yes	–	Yes	–																														
Tv	Movie shutter-priority AE	–	Yes	Yes	–																														
Av	Movie aperture-priority AE	Yes	–	–	Yes																														
M	Movie manual exposure	–	Yes	–	Yes																														

Exposure Compensation

Up to ±3 stops in 1/3- or 1/2-stop increments

* If AE Microadjustment is performed, the settable exposure compensation amount will decrease by the amount of the AE Microadjustment. For example, if you set the AE Microadjustment to +1 stop, the exposure compensation amount will be limited to a maximum +2 stops on the positive side.

Estimated Recording time, Movie Bit Rate, and File Size

Canon Log: OFF (H.264 / AVC)

Movie-recording Size			Total Recording Time (Approx.)			Movie Bit Rate / File Size (Approx.)
			64GB	256GB	1 TB	
5.5K RAW (5472 x 2886)	59.94 fps	RAW	3 min.	13 min.	50 min.	2600 Mbps 18711 MB/min.
	29.97 fps, 24.00 fps, 23.98 fps		4 min.	18 min.	1 hr. 13 min.	1800 Mbps 12937 MB/min.
4K DCI (4096 x 2160)	59.94 fps	ALL-I	9 min.	36 min.	2 hr. 21 min.	940 Mbps 6734 MB/min.
		IPB	36 min.	2 hr. 27 min.	9 hr. 35 min.	230 Mbps 1656 MB/min.
	29.97 fps, 24.00 fps, 23.98 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	1 hr. 10 min.	4 hr. 40 min.	18 hr. 17 min.	120 Mbps 869 MB/min.
4K DCI cropped (4096 x 2160)	59.94 fps	ALL-I	9 min.	36 min.	2 hr. 21 min.	940 Mbps 6734 MB/min.
		IPB	36 min.	2 hr. 27 min.	9 hr. 35 min.	230 Mbps 1656 MB/min.
	29.97 fps, 24.00 fps, 23.98 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	1 hr. 10 min.	4 hr. 40 min.	18 hr. 17 min.	120 Mbps 869 MB/min.
4K UHD (3840 X 2160)	59.94 fps	ALL-I	9 min.	36 min.	2 hr. 21 min.	940 Mbps 6734 MB/min.
		IPB	36 min.	2 hr. 27 min.	9 hr. 35 min.	230 Mbps 1656 MB/min.
	29.97 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	1 hr. 10 min.	4 hr. 40 min.	18 hr. 17 min.	120 Mbps 869 MB/min.
Full HD (1920 x 1080)	119.9 fps	ALL-I	23 min.	1 hr. 34 min.	6 hr. 8 min.	360 Mbps 2586 MB/min.
	59.94 fps	ALL-I	47 min.	3 hr. 8 min.	12 hr. 14 min.	180 Mbps 1298 MB/min.
		IPB	2 hr. 18 min.	9 hr. 14 min.	36 hr. 6 min.	60 Mbps 440 MB/min.
	29.97 fps	ALL-I	1 hr. 33 min.	6 hr. 12 min.	24 hr. 16 min.	90 Mbps 655 MB/min.
		IPB	4 hr. 30 min.	18 hr. 2 min.	70 hr. 27 min.	30 Mbps 226 MB/min.
		IPB (Light)	11 hr. 35 min.	46 hr. 23 min.	181 hr. 13 min.	12 Mbps 88 MB/min.

* Bit rate indicates video output only, audio is not included.

* Movie recording is interrupted if the maximum recording time per movie, 29 min. 59 sec., is exceeded. (Time is different for High Frame Rate movies.)

*Sound is not recorded for approx. the last two frames when the compression method for movie recording quality is IPB or IPB Light (audio: AAC) and [C. Fn 7-7 Audio compression] is set to [Enable]. The video and sound may be slightly out of sync when movies are played back in Windows.

Estimated Recording time, Movie Bit Rate, and File Size

Canon Log: ON (H.265 / HEVC)

Movie-recording Size			Total Recording Time (Approx.)			Movie Bit Rate / File Size (Approx.)
			64GB	256GB	1 TB	
4K DCI (4096 x 2160)	59.94 fps	ALL-I	8 min.	34 min.	2 hr. 13 min.	1000 Mbps 7164 MB/min.
		IPB	24 min.	1 hr. 39 min.	6 hr. 30 min.	340 Mbps 2443 MB/min.
	29.97 fps 24.00 fps 23.98 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	49 min.	3 hr. 18 min.	12 hr. 57 min.	170 Mbps 1227 MB/min.
4K DCI cropped (4096 x 2160)	59.94 fps	ALL-I	8 min.	34 min.	2 hr. 13 min.	1000 Mbps 7164 MB/min.
		IPB	24 min.	1 hr. 39 min.	6 hr. 30 min.	340 Mbps 2443 MB/min.
	29.97 fps 24.00 fps 23.98 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	49 min.	3 hr. 18 min.	12 hr. 57 min.	170 Mbps 1227 MB/min.
4K UHD (3840 X 2160)	59.94 fps	ALL-I	8 min.	34 min.	2 hr. 13 min.	1000 Mbps 7164 MB/min.
		IPB	24 min.	1 hr. 39 min.	6 hr. 30 min.	340 Mbps 2443 MB/min.
	29.97 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
		IPB	49 min.	3 hr. 18 min.	12 hr. 57 min.	170 Mbps 1227 MB/min.
Full HD (1920 x 1080)	119.9 fps	ALL-I	18 min.	1 hr. 12 min.	4 hr. 42 min.	470 Mbps 3373 MB/min.
	59.94 fps	ALL-I	49 min.	3 hr. 18 min.	12 hr. 57 min.	170 Mbps 1227 MB/min.
		IPB	1 hr. 33 min.	6 hr. 12 min.	24 hr. 16 min.	90 Mbps 655 MB/min.
	29.97 fps	ALL-I	1 hr. 2 min.	4 hr. 9 min.	16 hr. 16 min.	135 Mbps 977 MB/min.
		IPB	3 hr. 3 min.	12 hr. 13 min.	47 hr. 45 min.	45 Mbps 333 MB/min.
		IPB (Light)	7 hr. 47 min.	31 hr. 9 min.	121 hr. 41 min.	18 Mbps 131 MB/min.

LCD Screen					
Type	TFT color, liquid-crystal monitor				
Monitor Size	Size: 3.2-inches (aspect ratio 3:2) Diagonal: Approx. 3.15 in. / Approx. 8.01 cm Width: Approx. 2.63 in. / Approx. 6.67 cm Height: Approx. 1.75 in. / Approx. 4.44 cm				
Pixels	Approx. 2.1 million dots				
Touch-screen Operations	<ul style="list-style-type: none"> • AF Point Selection / Touch AF: Supported • Touch Shutter: Not supported • Menu setting touch control: Supported • Quick Control touch control: Supported • Touch-based menu magnified view: Supported • Touchscreen sensitivity: Standard / Sensitive / Disable • (VF shoot) Safety lock: ON / OFF (Default: ON) • Beep: Enable / Touch beep / Disable 				
Coverage	Approx. 100% vertically and horizontally Viewing angle: Approx. 170° vertically and horizontally				
Brightness Control	7 levels provided (manually adjustable, in Set-up Menu)				
Interface Languages	29 (English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Vietnamese, Hindi, Romanian, Ukraine, Turkish, Arabic, Thai, Simplified/Traditional Chinese, Korean, Malay, Indonesian, and Japanese)				
Playback Functions					
Display Format	<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 30%; text-align: center; vertical-align: middle;">Single Image Display</td> <td> <ul style="list-style-type: none"> • No information display • Basic information display • Available display items (1-10) • Detailed shooting information display <ul style="list-style-type: none"> ◦ Basic shooting information ◦ Lens information and RGB histogram ◦ White balance ◦ Picture Style ◦ Color space and noise reduction ◦ Lens aberration correction ◦ Record of sent images ◦ GPS* information ◦ IPTC information </td> </tr> <tr> <td style="text-align: center; vertical-align: middle;">Index Display</td> <td> <ul style="list-style-type: none"> • 4-image index • 9-image index • 36-image index • 100-image index </td> </tr> </tbody> </table> <p>* In certain countries and regions, the use of GPS may be restricted. Therefore be sure to use GPS in accordance with the laws and regulations of your country or region. Be particularly careful when traveling outside your home country. As a signal is received from GPS satellites, take sufficient measures when using in locations where the use of electronics is regulated.</p>	Single Image Display	<ul style="list-style-type: none"> • No information display • Basic information display • Available display items (1-10) • Detailed shooting information display <ul style="list-style-type: none"> ◦ Basic shooting information ◦ Lens information and RGB histogram ◦ White balance ◦ Picture Style ◦ Color space and noise reduction ◦ Lens aberration correction ◦ Record of sent images ◦ GPS* information ◦ IPTC information 	Index Display	<ul style="list-style-type: none"> • 4-image index • 9-image index • 36-image index • 100-image index
Single Image Display	<ul style="list-style-type: none"> • No information display • Basic information display • Available display items (1-10) • Detailed shooting information display <ul style="list-style-type: none"> ◦ Basic shooting information ◦ Lens information and RGB histogram ◦ White balance ◦ Picture Style ◦ Color space and noise reduction ◦ Lens aberration correction ◦ Record of sent images ◦ GPS* information ◦ IPTC information 				
Index Display	<ul style="list-style-type: none"> • 4-image index • 9-image index • 36-image index • 100-image index 				
Highlight Alert	On the single-image display, highlight areas without any image information will blink.				
Frame Grab from 4K Movies	<ul style="list-style-type: none"> • Individual frames in 4K movies recorded with the camera can be saved as JPEG still photos. • Approx. 8.8 megapixels (4096 x 2160) or approx. 8.3 megapixels (3840 x 2160) • Frame grab images cannot be resized or cropped in-camera. 				
Image Protection and Erase					
Protection	Erase protection: single image; select range; all images in folder; all images on card; all found images Unprotection: all images in folder; all images on card;				
Erase	Erase a single image, selected images, select range, all images in a folder, all images in a card or all found images.				
Direct Printing					

Compatible Printers	N/A (Direct printing not possible)															
DPOF: Digital Print Order Format																
DPOF	Version 1.1 compatible															
Direct Image Transfer																
Transferable Images	JPEG, RAW/C-RAW, HEIF images, and movies *Individual and multiple image files can be selected															
Customization																
Custom Functions	Total 38															
Custom Shooting Modes	<ul style="list-style-type: none"> • Current camera settings can be registered to C1, C2 and C3 in Set-up Menu (called-up for shooting on top LCD panel). • Automatic updating of the registered settings can be set to Enable or Diabile. * The saving of individual settings for still photos and movies is supported. 															
My Menu Registration	Up to six top-tier menu options and Custom Function settings can be registered. Up to five My Menu tabs can be added.															
External Interface																
USB Terminal	USB Type-C SuperSpeed Plus USB (USB 3.1 Gen 2) • For computer communication															
HDMI mini OUT Terminal	Type C (Resolution switches automatically) / CEC not compatible. • Images will not be displayed unless [NTSC] or [PAL] is properly set according to the video system of the TV set.															
Extension System Terminal	Wireless File Transmitter WFT-E9 * WFT-E6 and WFT-E8 are not supported.															
Power Source																
Battery	Battery Pack LP-E19 (supplied) * LP-E4N can be used, but the continuous shooting speed is restricted. * Due to multimedia regulations (IEC62368-1), charging of LP-E4N using LC-E19 battery charger included with the EOS-1D X Mark III camera, will be deprecated after December 20, 2020. * Batter Pack LP-E4 cannot be used.															
Number of Shots	Approx. (Based on CIPA testing standards) <table border="1" data-bbox="453 1331 1243 1535"> <thead> <tr> <th>Shooting Method</th> <th>Battery</th> <th>Temperature</th> <th>Possible Shots</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Viewfinder shooting</td> <td rowspan="4">Battery Pack LP-E19</td> <td>At 73°F/23°C</td> <td>2850</td> </tr> <tr> <td>At 32°F/0°C</td> <td>2360</td> </tr> <tr> <td rowspan="2">Live View shooting</td> <td>At 73°F/23°C</td> <td>610</td> </tr> <tr> <td>At 32°F/0°C</td> <td>530</td> </tr> </tbody> </table>	Shooting Method	Battery	Temperature	Possible Shots	Viewfinder shooting	Battery Pack LP-E19	At 73°F/23°C	2850	At 32°F/0°C	2360	Live View shooting	At 73°F/23°C	610	At 32°F/0°C	530
Shooting Method	Battery	Temperature	Possible Shots													
Viewfinder shooting	Battery Pack LP-E19	At 73°F/23°C	2850													
		At 32°F/0°C	2360													
Live View shooting		At 73°F/23°C	610													
		At 32°F/0°C	530													
Battery Check	4-level remaining charge display icon in viewfinder, top LCD panel, and LCD screen (when shooting info displayed) <ul style="list-style-type: none"> • Battery info. in Set-up Menu — % charge remaining, shutter count on current charge, and recharge performance displayed 															
Power Saving	Power turns off after the set time (1, 2, 4, 8, 15 or 30 min.) of non-operation elapses.															
Date/Time Battery	Rechargeable built-in secondary battery <ul style="list-style-type: none"> • Maintains date/time for approx. 1 month, if primary battery pack removed or depleted • Recharged by installation of charged LP-E19 or LP-E4N battery pack • Recharging time approx. 8 hours 															
Start-up Time	Approx. 0.2 sec. (Based on CIPA testing standards)															

Dimensions and Weight	
Dimensions (W x H x D)	Based on CIPA guidelines: Approx. 6.22 x 6.60 x 3.25 in. / 158.0 x 167.6 x 82.6mm (W x H x D)
Weight	Based on CIPA guidelines: Approx. 44.09 oz. / 1250g (Body only) Approx. 50.80 oz. / 1440g (Including battery, and memory card) * Weighed without body cap and eyecup.
Operating Environment	
Working Temperature Range	32–113°F/0–45°C
Working Humidity Range	85% or less