



# RF14-35mm F4 L IS USM

## Specifications

Lens	
<b>Focal Length</b>	14-35mm
<b>Maximum and Minimum Aperture</b>	F4-F22 (at all zoom settings)
<b>Lens Mount Type</b>	RF Mount; Metal Mount
<b>Minimum Focusing Distance</b>	7.9 in. (0.2m), at all zoom settings
<b>Maximum Magnification</b>	0.38x, at 35mm zoom setting • Fill frame with subject approx. 3.7 x 2.5 inches / 94 x 63mm in size, at 35mm zoom position
<b>Angle of View (Diagonal)</b>	114°00' – 63°00'
<b>Lens Construction</b>	16 elements in 12 groups
<b>Special Elements</b>	Three UD-glass elements, three Aspherical elements • Includes one UD Aspherical lens element
<b>Lens Coating</b>	• Canon SSC (Super Spectra Coating) • Canon SWC (Sub-wavelength Structure Coating) • Canon ASC (Air Sphere Coating) • Fluorine coating on front surface of front element
<b>Filter Size Diameter</b>	Ø77mm
<b>Aperture Blades</b>	9; circular shape
<b>Lens Switches</b>	AF/MF switch, Stabilizer ON/OFF switch
<b>Dust/Water Resistance</b>	Weather-resistant seals at lens mount, switches, zoom ring, focus ring, and Control Ring
<b>Focusing System</b>	Nano USM; rear focusing system
<b>Dual Pixel CMOS AF Coverage</b>	• EOS R, RP — approx. 88% (horizontal) x 100% (vertical)  • EOS R5, R6 Approx. 100% horizontal and vertical Face Detect + Tracking – approx. 100% x 100%
<b>Full-time Manual Focusing</b>	Yes (One-Shot AF only)
<b>Control Ring</b>	Yes • Click-stops provided (60 clicks/full revolution) • Click stops can be removed by Canon service facility, for a service fee.
<b>IS Mode Selection</b>	None (automatic panning detection provided)
<b>Optical Image Stabilization</b>	Provided • 5.5 stops optical IS correction with EOS R and RP • Conforms to CIPA test standards, using EOS R
<b>Coordinated IS (with EOS R5, R6)</b>	Up to 7 stops Coordinated IS correction • Conforms to CIPA test standards, using EOS R5

<b>Maximum Outer Diameter x Length</b>	Approx. ø3.3 in. x 3.9 in. (approx. ø84.1mm x 99.8mm) <ul style="list-style-type: none"> <li>• Minimum length at approx. 22mm zoom position</li> <li>• Maximum length at 35mm zoom position — approx. 4.25 in. / 107.9mm</li> </ul>
<b>Weight</b>	Approx. 1.2 lb. (approx. 19.0 oz. / 540g)
<b>Accessories</b>	
<b>Lens hood</b>	Canon EW-83P (Bayonet-mount with lock, petal type) (Bundled)
<b>Lens Cap</b>	Canon E-77 II (center pinch-type) (Bundled)
<b>Dust Cap</b>	Canon Lens Dust Cap RF (Bundled)
<b>Lens Case</b>	Canon Lens Case LP1219 (Bundled)
<b>RF Tele Extenders</b>	Not compatible
<b>EF Extension Tubes</b>	Not compatible
<b>Close-up Lenses</b>	Canon 250D — not compatible (no 77mm size) Canon 500D — 77mm compatible <ul style="list-style-type: none"> <li>• Close-up magnification range 0.07x–0.41x</li> </ul>
<b>Canon Gelatin Filter Holder IV</b>	Compatible (77mm adapter required) <ul style="list-style-type: none"> <li>• Usable number of hoods — 1</li> </ul>