



RF15-30mm F4.5-6.3 IS STM

Specifications

Lens	
Focal Length	15-30mm
Maximum and Minimum Aperture	f/4.5 - F22 (at 15mm zoom position) f/6.3 - F32 (at 30mm zoom position)
Lens Mount Type	RF Mount
Compatible Cameras	Canon EOS R-series, full-frame and APS-C
Minimum Focusing Distance	0.28m (11.0in) throughout zoom range, using AF 0.13m (5.1in) manual focus at 15mm zoom position
Maximum Magnification	0.16x (at 30mm zoom position) 0.52x (manual focus at 15mm zoom position)
Field of View, at Minimum Focus Distance	15mm – 16.5 x 11.0" (Approx. 421 x 281mm) 30mm – 9.0" x 6.0" (Approx. 229 x 153 mm)
Angle of View (Diagonal)	Approx. 110° 30' (15mm) Approx. 71° 35' (30mm)
Optical Design	
Lens Construction	13 elements in 11 groups
Special Elements	(Two) UD-glass elements, (One) Aspherical element
Lens Coating	Canon SSC (Super Spectra Coating)
Filter Size Diameter	ø67 mm
Aperture Blades	7
Image Stabilization	5.0 stops correction with In-lens Optical Image Stabilization (7.0 stops correction with EOS R3/R5 in-body coordinated Image stabilization)
Focusing	
Focusing Drive System	Canon STM (Leadscrew type STM)
Full-time Manual Focusing	Yes (Supports both ONE SHOT AF and SERVO AF with compatible EOS R-series cameras)
Dual Pixel CMOS AF Coverage (Horizontal x Vertical)	<ul style="list-style-type: none">• EOS R/RP — Approx. 100% x 88%• EOS R5/R6 — Approx. 100% x 100%• EOS R7/R10 — Approx. 100% x 100%
Exterior Design	
Control Ring	Combination Control Ring/Manual Focus Ring <ul style="list-style-type: none">• Selectable via switch on lens barrel• No clicks, when used as Control Ring
Manual Focus Ring	Combined MF/Control Ring on lens
AF/MF Switch	None — selected via camera menu, or AF/MF switch on compatible EOS R-series cameras

MF/Control Ring Switch	Yes, on lens barrel
Distance Scale	Yes • Available in EVF or Live View LCD screen of compatible EOS R-series cameras
Distance Limiter Switch	None
Dust / Weather Resistant Construction	None
Dimensions, Weight	
Maximum Outer Diameter x Length	Approx. ø3.0 in. x 3.5 in. (ø76.6mm x 88.4mm)
Weight	Approx. 13.6 oz. / 0.9 lb. / 390g
Accessories	
Lens hood	Canon EW-73E • Bayonet-mount, petal-shaped hood • Optional accessory, sold separately
Lens Cap	(Front) Canon E-67 II (Bundled)
Dust Cap	(Rear) Canon Lens Dust Cap RF (Bundled)
Lens Case	Canon Lens Case LP1116 • Optional accessory, sold separately
Extension Tubes	None (No Canon RF mount extension tubes)
Close-up Lenses 250D / 500D	Not compatible (No ø67mm close-up lenses)
Canon RF Extender 1.4x/2x	Not compatible